

CILLUX LED LIGHTING

EXPLOSION PROOF LIGHTS / Explosion Proof Series Type 2



Model	EXP-T217-10W	EXP-T218-19W	EXP-T219-38W
LED Brand	Cree	Cree	Cree
LED (pcs)	90 pcs	180 pcs	360 pcs
Color	5500K	5500K	5500K
CRI	>80	>80	>80
Connector	-	-	-
Rated Power	10W	19W	38W
Replacement	-	-	-
EEL	-	-	-
Useful Lumens	900LM±10%	1800LM±10%	3600LM±10%

FEATURES

- Colour temperature 3000K and 4500K also available
- Input Voltage options: AC/DC 100-277 V, DC 12 / 24 V

W	mA	Power Factor	Input Voltage	Beam Angle	IP	Product Dimensions (mm)	Packaging Type	Outer Carton Dimensions (mm)	Pcs per Carton	G.W/ Carton (kgs)	Working Lifetime	Warranty
10W	250	>0.9	check features	180°	IP65	235*125*70	Carton	350*310*340	1 pc	13.5	60000 hrs	5 yrs
19W	520	>0.9	check features	180°	IP65	435*125*70	Carton	500*310*340	1 pc	15.8	60000 hrs	5 yrs
38W	1050	>0.9	check features	180°	IP65	635*125*70	Carton	700*310*340	1 pc	21.2	60000 hrs	5 yrs